

## B500 UV Curing Chamber

The INCURE B500 is a fully enclosed curing chamber that features 360 degree shielding for maximum UV protection. Just place the F100P/F200P on top of the chamber and start curing – no tools required!

This uv chamber includes a door interlock for use with the F100P/F200P system, which automatically causes the unit's shutter to close when the door is opened. Dual rear panel Dsub connectors allow pass through of F100P/F200P control signals for use with a PC, PLC, shutter control foot pedal, external interlock, etc.

Comes with an adjustable height curing tray which allows for 5 repeatable curing distances, and a door mounted lamp-ON indicator.



<b>Model</b>	B500	
<b>General</b>	Cooling	Forced air w/louvers, channeled from lamp head
	Interconnect cable	Dual 15 position DSUB, Male/Female, 1.25 ft.
<b>Cure Distance</b> (inches)	Shelf positions	1.75", 3.5", 5.25", 7.0" (bottom of lamp to shelf)
	Distance to floor	9" (bottom of lamp to floor)
<b>Dimensions</b> H x W x D (inches)	Internal	9" x 9" x 10.4" w/adjustable shelf
	External	11.8" x 11.6" x 12.1" D = 13.3 w/door handle
	Weight (lbs.)	9 pounds (without lamp head)